




FEATURES:

- Light but solid shell is easy to release heat
- Waterproof push button with emergency stop
- Canvas chain bag, light and durable
- G80/100 ultra heat-treatable alloy steel chain, has a high resistance to wear and corrosion
- Standard lifting height- 5mtrs and can be customized
- Load hook is forged carbon steel hook with a heavy-duty latch. Antirust bearing in hook allows 360 degree rotation to prevent twisting of load chain.

Dimension & Specification



ARMSTRONG SINGLE SPEED CHAIN HOIST

VOLTAGE: 3 PHASE 415V 50HZ

Item NO.	HH-B05	HH-B10	HH-B20	HH-B30	HH-B50	
Rated Load (ton)	0.5	1	2	3	5	
Standard Lift (m)	3	3	3	3	3	
Lifting Speed (m/min)	7	7	3.5	4	2.6	
Output (kw)	0.8	1.6	1.6	3	3	
Power Supply	3P/415V/50HZ					
INS Class	F					
%ED	30%					
Dimension of Load chain	φ7.1X 21			φ9×27		
Strands of Load chain	1	1	2	2	3	
Test load (ton)	0.625	1.25	2.5	3.75	6.25	
Cable Length(m)	2.5	2.5	2.5	3	3	
Net Weight (kg)	50	55	60	98	103	
Extra weight per meter of extra lift (kg)	1.1	1.1	2.2	3.4	5.3	
Minimum headroom (mm)	500	550	630	800	850	
Main dimensions	A (mm)	245	245	245	265	265
	B (mm)	245	245	245	265	265
	C (mm)	158	158	124	127	127
	D (mm)	142	142	176	205	205
	E (mm)	350	350	350	393	393
	F (mm)	600	600	610	738	738

HH-B Electric Chain Hoist

HH-B electric chain hoist is a new kind of product we developed recently. It has such characteristics as fast lifting speed, convenient operation and beautiful appearance. Especially its unique overloading safety protection setting and electrical machine hot protection setting make sure of the higher reliability of this product. It is widely used in lifting light and small goods. It can also be used in low-level space materials circulation system by mating with aerial travelling crane equipment. This product attests to be effective equipment which can improve working condition and enhance labor efficiency. Optional wireless remote controller.

Powered by
ARMSTRONG INDUSTRIES LIMITED



TROSX FLOW CONTROL SDN BHD

(Co. No. 1237109-A)
No. 39, Jalan Industri Mas 2, Taman Mas,
47130 Puchong, Selangor Darul Ehsan, Malaysia.
Tel: 6016-322 0390 Fax: 603-8068 3990
Email: sales@troscfc.com
(GST No: 000397651968)