



TROSX FLOW CONTROL SDN BHD

(Co. No. 1237109-A)
 No. 39, Jalan Industri Mas 2, Taman Mas,
 47130 Puchong, Selangor Darul Ehsan, Malaysia.
 Tel: 6016-322 0390 Fax: 603-8068 3990
 Email: sales@trosxfc.com
 (GST No: 000397651968)

Steel Shaft

It is used for cleaning of tube by transmitting power in terms of rotation from the motor unit to tools head cutter or brush within tube.

Inner Core

It is flexible wire with multiple wound opposite layer. It is made of high tensile spring steel or stainless steel (as per requirement) and passed through heat treatment process to make it absolutely vibration free.

Outer Casing

It is flexible ,double interlock ,circular rounded, made of galvanized steel strip , special spring steel lining is provided within outer casing to avoid any friction between inner core & outer casing .

Connection

One end of shaft with machine end socket is attached to suitable motor and other end is attached to tool end.



Inner Core Dia mm (Inch)	12-13mm (1/2")	15-16 mm (5/8")	19.0 mm (3/4")	20.0 mm		
Outer Casing mm (Inch)	24.0 mm (15/16")	29.0 mm (1.1/4")	33.0 mm (1.3")	34.0 mm		
Length						
Mtrs.	Feets	Sr.No.	Model No.	Model No.	Model No.	Model No.
6.0	20.0	1	BTS-105-20	BTS -106-20	BTS -107-20	BTS -108-20
7.5	25.0	2	BTS-105-25	BTS 106-25	BTS -107-25	BTS -108-25
8.0	27.0	3	BTS-105-27	BTS -106-27	BTS -107-27	BTS -108-27
9.0	30.0	4	BTS-105-30	LBFS-106-30	BTS -107-30	BTS -108-30
10.0	33.0	5	BTS-105-33	BTS -106-33	BTS -107-33	BTS -108-33
12.0	40.0	6	BTS-105-40	BTS -106-40	BTS -107-40	BTS -108-40
15.0	50.0	7	BTS-105-50	BTS -106-50	BTS -107-50	BTS -108-50
18.0	60.0	8	BTS-105-60	BTS -106-60	BTS -107-60	BTS -108-60
20.0	65.0	9	BTS-105-65	BTS -106-65	BTS -107-65	BTS -108-65
25.0	82.5	10	BTS-105-82	BTS -106-82	BTS -107-82	BTS -108-82
30.0	100.0	11	BTS-105-100	BTS -106-100	BTS-107-100	BTS -108-100
Spare Inner Core Per Meter			BTIC-105	BTIC-106	BTIC-107	BTIC-108
Spare Outer Casing Per Meter			LBOC-105	LBOC-106	LBOC-107	LBOC-108
Spare Hand Piece			LBHP-105	LBHP-106	LBHP-107	LBHP-108